

Preformed Guy-Grips Deadends

Preformed Guy Grip Deadend

function as termination solution for short span. Generally, preformed is meant to use in low voltage environment. Preformed light load offer economic solution, not requiring extra equipments for installation.

Preformed guy-grip dead end uniformly transferring the load from the cable unto the deadend loop.

Sizing Code	Strand 7 - wire Mean Dia. Inches (mm.)	Length* Inches (cm.)	Colour code	Breaking Strength		Std.Pkg Pcs/Bx
				pounds	Kgf.	
2 M	1/8 (3.18)	17 (43.18)	White	1,830	830	50
2.5 M	9/32 (3.97)	18 (45.72)	Blue	2,940	1,333	50
3 M	3/16 (4.76)	20 (50.80)	Red	3,990	1,809	50
4 M	1/4 (6.35)	25 (63.50)	Yellow	6,650	3,018	50
6 M	5/16 (7.94)	31 (78.74)	Black	11,200	5,079	50
10 M	3/8 (9.53)	35 (88.90)	Orange	15,400	6,984	50
70 mm2	7/16 (11.11)	38 (96.52)	Green	20,800	9,433	50



Preformed Suspension ADSS OFC

Safety Concern

The product is meant for single use but may be reapplied for tensioning within 90 days of the installation.

Product modification is prohibited.

Product is intended to be use by qualified personnel only.

When applying preformed product on energized line, appropriate safety equipment are required.

Preformed products' performance are susceptible to decline without proper handling.

